

GENESIS VERTICAL LIFT

ENCLOSURE AND SHAFTWAY MODELS









The Garaventa Genesis is a vertical platform lift designed to provide access into or within public buildings. It travels inside a complete, self-contained enclosure, as shown, or can be located in a shaftway constructed by others. Our unique, anodized aluminum design is strong, durable and attractive.

The Genesis Shaftway model fits inside a vertical runway that is built by others in accordance to Garaventa Lift specifications. The system consists of a drive mast, passenger platform and doors or gates. The shaftway can be completely enclosed, much like an elevator shaftway, or it can be open at the upper landing. A variety of doors and gates are available.




Shaftway Straight Through

Platform	Shaftway	Shaftway	Platform	Platform
Size	Width	Length	Width	Length
Compact	1317mm	1295mm	914mm	1257mm
	[51 7/8"]	[51"]	[36"]	[49 1/2"]
Standard	1394mm	1407mm	992mm	1370mm
	[54 7/8"]	[55 3/8"]	[39"]	[53 7/8"]
Mid-Size	1394mm	1558mm	992mm	1520mm
	[54 7/8"]	[61 3/8"]	[39"]	[59 7/8"]
Large	1546mm	1558mm	1146mm	1520mm
	[60 7/8"]	[61 3/8"]	[45"]	[59 7/8"]



Shaftway 90° Entry / Exit

Platform	Shaftway	Shaftway	Platform	Platform
Size	Width	Length	Width	Length
Compact	1272mm	1316mm	940mm	1208mm
	[50 1/8"]	[51 3/4"]	[37"]	[47 1/2"]
Standard	1350mm	1428mm	1017mm	1320mm
	[53 1/8"]	[56 1/4"]	[40"]	[52"]
Mid-Size	1350mm	1579mm	1017mm	1471mm
	[53 1/8"]	[62 1/8"]	[40"]	[57 7/8"]
Large	1502mm	1579mm	1169mm	1471mm
	[59 1/8"]	[62 1/8"]	[46"]	[57 7/8"]



Shaftway On/Off Same Side

Platform	Shaftway	Shaftway	Platform	Platform
Size	Width	Length	Width	Length
Compact	1317mm	1316mm	914mm	1208mm
	[51 7/8"]	[51 3/4"]	[36"]	[47 1/2"]
Standard	1394mm	1428mm	992mm	1320mm
	[54 7/8"]	[56 1/4"]	[39"]	[52"]
Mid-Size	1394mm	1579mm	992mm	1471mm
	[54 7/8"]	[62 1/8"]	[39"]	[57 7/8"]
Large	1546mm	1579mm	1144mm	1471mm
	[60 7/8"]	[62 1/8"]	[45"]	[57 7/8"]


• Platform dimensions are clear inside dimensions.

SHAFTWAY WIDTH

- Ramp required for floor mount
- Mast-to-wall attachment required
- [Shaftway Only] If the tie back rail (spreader bar) is to be used to attach the mast to the shaftway wall, the shaftway width dimension will increase by 38 mm [1 1/2"]




ENCLOSURE MODEL




The Genesis Enclosure model is a complete, self-contained vertical access solution. It is similar to the Shaftway Model except it includes a pre-fabricated enclosure and integrated doors or gates. The enclosure can be built full height and fitted with a Plexiglas dome for weather protection, or can be left open at the top.






Platform	Base	Base	Platform	Platform
Size	Width	Length	Width	Length
Standard	1399mm	1505mm	947mm	1370mm
	[55 1/8"]	[59 1/4"]	[37 1/4"]	[53 7/8"]
Mid-Size	1399mm	1656mm	947mm	1520mm
	[55 1/8"]	[65 1/8"]	[37 1/4"]	[59 7/8"]
Large	1551mm	1656mm	1099mm	1520mm
	[61 1/8"]	[65 1/8"]	[43 1/4"]	[59 7/8"]

Enclosure 90° Entry / Exit



Platform	Base	Base	Platform	Platform
Size	Width	Length	Width	Length
Standard	1399mm	1505mm	1017mm	1295mm
	[55 1/8"]	[59 1/4"]	[40"]	[51"]
Mid-Size	1399mm	1656mm	1017mm	1446mm
	[55 1/8"]	[65 1/8"]	[40"]	[56 7/8"]
Large	1551mm	1656mm	1155mm	1446mm
	[61 1/8"]	[65 1/8"]	[45 1/2"]	[56 7/8"]

Enclosure On/Off Same Side



Platform	Base	Base	Platform	Platform
Size	Width	Length	Width	Length
Standard	1399mm	1505mm	947mm	1295mm
	[55 1/8"]	[59 1/4"]	[37 1/4"]	[51"]
Mid-Size	1399mm	1656mm	947mm	1446mm
	[55 1/8"]	[65 1/8"]	[37 1/4"]	[56 7/8"]
Large	1551mm	1656mm	1099mm	1446mm
	[61 1/8"]	[65 1/8"]	[43 1/4"]	[56 7/8"]

^{*}For more detailed information refer to the Genesis Design and Planning Guide



GENESIS VERTICAL LIFT

Need Design Assistance? Call your local Garaventa Lift representative or our Design Hotline at 1.800.663.6556

Assistance?	or our Design Hotline at 1.800.663.6556
TECHNICAL INFO	DRMATION
Rated Load: Standard 7	750 lbs (340 kg) with a safety factor of 5
Speed: Leadscrew - 3 m	neters (10 ft) per minute at full load Hydraulic - 5.2 meters (17 ft) per minute at full load
Travel Range: Leadscre	ew - up to 12 feet Hydraulic - up to 14 feet
Sturdy 16 gauge galvan	venta doors and gates equipped with Garaventa interlocks and internal closers for doors and gates ized steel platform side walls 1070mm (42 1/8") Constant pressure directional control switches lible emergency stop switch Full length grab rail on platform side wall panel
	em: Motor: 2 HP (1750 RPM) Motor Drive Type: ACME screw (1" diameter) Mains Supply: 120 VAC on a dedicated 20 amp circuit, International Models: 208-240 VAC on a dedicated
Hydraulic (Dual 5/8" AN	m: Motor: 3 HP (2.2 KW) complete with auxiliary power system Motor Drive Type: Chained SI 50 chains) Mains Supply: North American Models 120 VAC on a dedicated 15 amp circuit, 8-240 VAC on a dedicated 16 amp circuit
Controls: Keyless Cont switches Control Volt	rols (No key required for call stations and platform controls) Directional Controls - Constant pressure tage: 24 VDC
Power Requirements:	120 VAC single phase Optional 208-240 VAC single phase
constant pressure directic Choice of RAL colors Au powered emergency lowe	er Door Operators (ANSI/ BHMA A156.19 compliant) Custom platform sizes available Illuminated and tactile on all buttons Arrival gong and digital floor display Steel or Plexiglas enclosure panels (Enclosure only) utodialer phone (ADA compliant) Keyed operation Custom applications (Consult Garaventa Lift) Battery ering (Leadscrew drive only) Full time battery operation ***suitable for low use applications ONLY and Ventilation System with thermostatic controls - requires Continuous Mains Power (Enclosure only)
Warranty: 2 year stand	lard warranty Optional additional 5 year extended warranty (7 years)
	Contact us today Printed in Canada 15805-Q-PB

Authorized Garaventa Lift Representative

Phone: +1 604 594 0422
Toll Free: 1 800 663 6556
Web site: www.garaventalift.com

© Garaventa Lift. As we are continuously improving our products, specifications outlined in this brochure are subject to change without notice.